

Category

Name

# Logistics 12.2 Bulk Water Carrier

Mobility

Mass Class



## Standard Specification

Crew Capacity	Provision for two (2) crew
Dimensions	8550 L x 3210 H x 2880 W mm (2900 W mm mirror to mirror)
Weight	22,400kg
Cab Chassis	Isuzu FVZ260-300 6x4 / 30,000 kg GVM / Single cab / 221kW diesel engine / automatic transmission
Crew Protection	AVL, Burn over blankets, Radiant Heat Shields, In-cab Air
Pump	Waterous CLV with K transmission c/w hydraulic piston motor
Pump Performance	1400 L/m @ engine idle speed (120 kPa)
Pumping Modes	Stationary
Primer Pump	Electric primer
Foam System	N/A
Deliveries	Four (4) x 64mm BIC Female
Collectors	Nil
Drafting	One (1) x 100mm Storz Hard Suction
Tank Fill	Two (2) x 64mm BIC Male tank fill
Hose Reels	N/A
Water Capacity	12,000 litres of water
Lighting	24 volt LED Lighting
Welfare	Fridge 35 ltr
Equipment	7500 litre collar tank (on trolley) Portable pump GAAM MK4QF Honda GX390 500 kg cantilever side lift Portable lighting

Primary  
Incident

Services



[Click here](#) to view Walk Around video