

Category

Name

Tanker 2.4 Broadacre Tanker

Mobility

Mass Class



Standard Specification

Crew Capacity	Provision for three (3) crew
Dimensions	7000 L x 3000 H x 2490 W mm (2900 W mm mirror to mirror)
Weight	TBC
Cab Chassis	Isuzu FSS 110-210 4x4 / 11,000 kg GVM / Single cab / 154 kW diesel engine / manual transmission
Crew Protection	AVL, Deluge, Radiant heat shields, Lagging, Burn over blankets and In cab air units
Pump	Cast iron, bronze impeller, centrifugal type pump independently driven by an IC diesel engine
Pump Performance	1200 L/m @ 700 kPa
Pumping Modes	Stationary / Pump and Roll
Primer Pump	Hand priming diaphragm type
Foam System	A Class Around the pump (ATP)
Deliveries	Two (2) x 64mm BIC Female
Collectors	One (1) x 64mm BIC Male tank fill One (1) x 65mm Camlock suction
Hose Reels	One (1) electric rewind 50m x Ø25mm One (1) electric rewind 30m x Ø19mm
Water Capacity	2600 litres (2000 litres operational / 600 litres deluge)
Foam Capacity	40 litre A Class foam in 2 x 20 litre drums
Lighting	24 volt LED Lighting
Welfare	Fridge

Primary Incident



Bushfire

Services

