

Category

Name

Tanker 3.4 Urban Tanker

Mobility

Mass Class



Services



Standard Specification

Crew Capacity	Provision for six (6) crew
Dimensions	8072 L x 3024 H x 2490 W mm (2900 W mm mirror to mirror)
Weight	14,010 kg
Cab Chassis	Isuzu FTS 139-260 4x4 / 14,200 kg GVM / Crew cab / 191kw diesel engine / automatic transmission
Crew Protection	AVL, Deluge, Radiant heat shields, Lagging, Burn over blankets and In cab air units
Pump	Waterous CLVT close coupled to an independent 4 cyl water cooled Isuzu 4JG1TPW-01 Engine
Pump Performance	1850 L/m @ 700 kPa
Pumping Modes	Stationary / Pump and Roll
Primer Pump	Electrically powered (Oil less) vane type
Foam System	A Class Injected
Deliveries	Three (3) x 64mm BIC Female
Collectors	Two (2) x 64mm BIC Male One (1) x 100mm Storz Hard Suction One (1) x 64mm BIC Male Tank fill (direct)
Hose Reels	One (1) electric rewind 50m x Ø25mm One (1) electric rewind 30m x Ø19mm
Water Capacity	3600 litres (3000 litres operational / 600 litres deluge)
Foam Capacity	60 litres A Class foam tank
Lighting	24 volt LED Lighting
Ladder	Arion 7.65 triple extension / Little Giant
Welfare	32 litre fridge

Configurations

BA equipped	4 x BA set stowage 4 x spare BA cylinder stowage B Class foam induction post delivery 200 litres B Class foam tank
-------------	---

Primary Incident



Bushfire



Structure Fire (external)



Structure Fire (internal)

[Click here](#) to view Walk Around video