



FOR A SAFER STATE

Category

Name

## Pumper Urban Pumper Type 2

Mobility

4x2

**Mass Class** 





## **Services**





## Standard Specification

**Crew Capacity** Provision for six (6) crew 8010 L x 2974 H x 2400 W mm **Dimensions** 

(2900 W mm mirror to mirror)

Weight TBC

**Cab Chassis** Isuzu FTR 150-260 4x2 / 15,000 kg GVM /

Crew cab / 191kW diesel engine /

automatic transmission

Crew Protection AVL. Burn over blankets

Waterous CGV pump/transmission Pump

**Pump Performance** 3000 L/m @ 1000 kPa Stationary / Pump and Roll **Pumping Modes** 

**Primer Pump** Electric vane type

Foam System A Class Injected, B Class inducted post-

delivery

Four (4) x 64mm BIC Female Deliveries Three (3) x 64mm BIC Male Collectors One (1) x 64mm tank fill

Two (2) x 125mm Storz hard suction

Hose Reels Two (2) electric rewind 60m x Ø25mm

**Water Capacity** 1200 litres

**Foam Capacity** 60 litre A Class foam tank 200 litres B Class foam tank

Lighting 24 volt LED Lighting

9.0m double extension / Little Giant Ladder

Welfare Fridge

Four (4) x BA sets Equipment

## **Primary** Incident



Structure Fire



Road Crash



**HAZMAT**