

Category

Name

Pumper Urban Pumper Type 3





Standard Specification	
Crew Capacity	Provision for six (6) crew
Dimensions	7900 L x 3100 H x 2490 W mm
	(2900 W mm mirror to mirror)
Weight	11,950 kg
Cab Chassis	lsuzu FTS 139-260 4x4 / 13,900kg GVM /
	Crew cab / 191 kW diesel engine / 6 speed automatic transmission
Crew Protection	AVL, Radiant Heat Shields, Chassis Lagging,
	Burn over blankets and In Cab Air
Pump	Waterous CLS with K type transmission
Pump Performance	1800 L/m @ 1000 kPa
Pumping Modes	Stationary / Pump and Roll
Primer Pump	Electric vane type
Foam System	A Class Injected, B Class inducted post-
	delivery
Deliveries	Three (3) x 64mm BIC Female
Collectors	Three (3) x 64mm BIC Male
	One (1) x 64mm tank fill
	Two (2) x 100mm Storz hard suction
Hose Reels	Two (2) electric rewind 50m x Ø25mm
Water Capacity	1400 litres
Foam Capacity	60 litre A class foam tank
	200 litre B Class foam tank
Lighting	24 volt LED Lighting
Ladder	Arion 7.65 triple extension / Little Giant
Welfare	Front opening fridge in locker
Equipment	Four (4) x BA sets on pantograph

Two (2) x BA sets spare

Primary Incident



HAZMAT

Services





Click Here to view Walk Around Video

Version 3.0 30/06/2020 CM Ref: 19/183855